

POLINTEK® Impeller Blades – High Duty & Chemical Resistance

SECTION 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT NAME :

POLINTEK® Impeller Blades – High Duty & Chemical Resistance

OTHER NAME :

Impeller

RECOMMENDED USE :

Thermoplastics component system. Product designed for rotating system and provide excellence physical, chemical and environment properties . Please refer to the relevant POLINTEK® Instructions For Use for further information. For use only by professional operators.

COMPANY NAME :

PT. Darta Mckuadrat Industri

ADDRESS :

Jl. Raya Puspitek No. 147 RT 014/ 004 Kelurahan Setu, Kecamatan Setu Tangerang Selatan, Banten 15314

TELEPHONE NO :

+6221 75877805

SECTION 2 – HAZARD IDENTIFICATION

The most important hazards and effects: None

Skin contact: Essentially non-irritating to skin

Eye contact: Solid or powder may cause irritation by an abrasive action of solid or powder.

Inhalation: PPS resin under normal processing temperatures (330°C - 330°C) releases very little gases, which has a irritation property. However, if the temperature exceeds 360°C, decomposition will occur rapidly and release of carbon oxides, sulfur dioxide occurred resulting in acute lethality.

Ingestion: Oral toxicity is very low.

Environmental effects: None

Physical and chemical hazards: Not applicable

Specific hazards: Not applicable

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical identity of ingredients	CAS Number for ingredients
PPS	26125-40-6
Glass fiber	65997-17-3

*The specific chemical identity/proportion of this component is considered trade secret information in accordance with 29 CFR 1910.1200

PT. DARTA MCKUADRAT INDUSTRI

Jl. Raya Puspitek No. 147 RT 014/ 004 Kelurahan Setu, Kecamatan Setu Tangerang Selatan, Banten 15314 Telp: +6221 75877805

www.darta.co.id

POLINTEK® Impeller Blades – High Duty & Chemical Resistance

SECTION 4 – FIRST AID MEASURES

Skin contact: Flush the skin with running water. For skin contact with fume condensation, immediately wash the affected area thoroughly with soap and water. For skin contact with molten plastic, immediately cool with water and seek medical attention.

Eye contact: Immediately irrigate the affected eye(s) with clean water for at least 15 minutes. Do not rub eye(s) to prevent irritation and damages to cornea(s). If irritation develops or persists, obtain medical attention.

Inhalation: Remove the victim from the area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention if any breathing difficulty persists.

Ingestion: Not a likely route of exposure. If swallowed, seek medical attention.

Note: Several thermal burns can result from contact with molten immediately

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing media: Water spray, dry chemical, chemical foam, and carbon dioxide.

Hazardous Combustion Products: This material is a combustible thermoplastic, which will melt and drip when ignited and give combustion products.

Fire Fighting: Firefighters should wear protective clothing and use self-contained breathing apparatus when fighting fire involving this material.

Explosive: Not explosive.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions: Pellets spilled on the floor can cause slipping.

Environmental precautions: PPS resin is a stable organic thermoplastic and a hazardous polymerization will not occur.

Recovery: To prevent the danger of slipping or falling, sweep up or vacuum the spilled materials and place them in a proper waste container for disposal.

SECTION 7 – HANDLING AND STORAGE

Handling: Always wear recommended personal protective equipment. Wash thoroughly after handling. Launder contaminated clothing before reuse. Long retention at high temperature can cause heat decomposition. Spilled pellets on a floor can cause a slip.

Prevention of user exposure: Gases generated in the moulding process may cause irritation to the skin and respiratory tract. Avoid dust or pellets in contact with eyes. Do not touch molten resin to prevent a burn.

Prevention of fire and explosion: PPS resin will not ignite itself at normal temperature but keep fire away wherever and whenever possible.

Measures to prevent dust generation: Use local exhaust ventilation. Avoid breathing thermal

PT. DARTA MCKUADRAT INDUSTRI

Jl. Raya Puspitek No. 147 RT 014/ 004 Kelurahan Setu, Kecamatan Setu Tangerang Selatan, Banten 15314 Telp: +6221 75877805

www.darta.co.id

POLINTEK® Impeller Blades – High Duty & Chemical Resistance

processing fume vapor.

Storage: PPS resin will not degrade during storage. While heating and/or cooling is not required, the resin should be stored indoor to protect it from rain or excessive moisture. Periodically check storage for vertical stability and/or container damage or fatigue. Store resin in clean, dry environment in sealed containers. Avoid storing flammable materials in the resin storage area.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

ACGIH – None listed

OSHA – None listed

Engineering controls: Thermal processing equipment should be ventilated to control gas and fume given off when the resin is heated to extrusion or injection molding temperatures. For most operations, a continuous supply of fresh air to the general workplace area along with the continuous removal of processing fume contaminated air through a local exhaust ventilation system will be adequate. However, the ventilation requirements must be determined on an individual basis for each workplace.

Eye protection: Wear safety glasses with side shields or chemical safety goggles as described by OSHA's eye and face protection regulations.

Skin and body Protection: None required in normal handling of pellets. When handling the hot resin (extruded, air shots or parts), well-insulated gloves are to be worn to prevent thermal burns.

Respiratory Protection: None required in normal handling of pellets. In handling of resins that may be reinforced with fiberglass, it may be necessary to wear a NIOSH / MSHA approved dust respirator if the airborne dust concentration is near or exceeds the nuisance dust.

Ingestion: No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pellets

Physical State: Solid

Flash Point: Over 500 °C

Melting point: 280 °C

Boiling point: Not available

Vapor Pressure: Not available

Specific Gravity: 1.66

Solubility: Insoluble in water

Upper flame limit: Not available

PT. DARTA MCKUADRAT INDUSTRI

Jl. Raya Puspitek No. 147 RT 014/ 004 Kelurahan Setu, Kecamatan Setu Tangerang Selatan, Banten 15314 Telp: +6221 75877805

www.darta.co.id

POLINTEK® Impeller Blades – High Duty & Chemical Resistance

Lower flame limit: Not available

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable under normal temperatures and pressures.

Reactivity: Not reactive under recommended conditions of handling, storage, processing and use.

Conditions to avoid: Incompatible materials, dust generation, strong oxidants.

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide, carbon dioxide, sulfur dioxide, Irritating and toxic fumes, smoke and fume.

Hazardous Polymerization: Has not been reported

Storage stability: Stable

Reactivity in water: None

Oxidizing property: None

Self-reactivity / Potential for explosion: None

SECTION 11 – TOXICOLOGICAL INFORMATION

Acute inhalation: Processing fumes from similar materials are not considered toxic. There were no distinct or consistent treatment related tissue or organ changes noted in gross necropsies.

Acute toxicity: No data available

Sensitization and chronic toxicity: No data available

SECTION 12 – ECOLOGICAL INFORMATION

The material, which is resistant to biodegradation and insoluble in water, is expected to present any ecologically significant problems and not considered degradable or toxic in terms of their physical impact. Pellets left at large (spills) in the general environment may be ingested by animals. Do not dispose any of the material into marine or water area to prevent marine animals or birds from ingestion.

SECTION 13 – DISPOSAL CONSIDERATION

Comply with all applicable national and local laws or regulations. Do not dispose into sewers, ground or body of water. Preferred options for disposal are recycle, incineration with energy recovery and landfill. Remove all packaging for recovery or waste disposal.

SECTION 14 – TRANSPORT INFORMATION

Comply with all applicable national and local laws or regulations. Avoid water and careless handling to prevent damage to the container. Watch your step not to slip in the event that pellets spill out of the torn container.

International regulations for transport:

US DOT - Not applicable

PT. DARTA MCKUADRAT INDUSTRI

Jl. Raya Puspitek No. 147 RT 014/ 004 Kelurahan Setu, Kecamatan Setu Tangerang Selatan, Banten 15314 Telp: +6221 75877805

www.darta.co.id

POLINTEK® Impeller Blades – High Duty & Chemical Resistance

IMO - Not applicable
IATA - Not applicable
RID/ADR - Not applicable
Canadian TDG - Not applicable

SECTION 15 – REGULATORY INFORMATION

Comply with all national and local regulations.

SECTION 16 – OTHER INFORMATION

1) Uses :

- Recommended use: Manufacturer of articles by injection and extrusion.
- Prohibited use: For special application e.g. in medicine, surgery, or the food industry, obtain further information from the manufacturer.

2) Registration numbers: The polymers are not listed in the EINECS inventory. All the other constituents of this preparation are registered in the 'EINECS' inventory.

IMPORTANT NOTES

1. To the best of our knowledge this document complies with the National Code of Practice for the Preparation of Material Safety Data Sheets.
2. This material safety data sheet summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this material safety data sheet and consider the information in the context of how the product will be handled and used in the workplace, including in conjunction with other products.
3. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact the Safety and Emergency Services Department.
4. Our responsibility for products sold, is subject to our terms and conditions, a copy of which is sent to our customers, and is also available on request.